




1. What is Paint Protection Film?

- ▲ Multi-layer Paint Protection Film
- Mass variety coverage for both Exterior and Interior
- ▲ Available in both transparent and Matte finish
- ▲ Ultimate protection solution for paint surface
- ▲ Protect and retain your vehicle a brand-new look



Benefits of PPF



Self Healing



Scratches Resistance



Anti-Rock Chips



Anti-UV & Oxidation



Hydrophobic



Make Maintenance Easy

2. Where should you apply? (interior)



Gloss Panels



Smooth/ Gloss Textured Panels



Textured Panels

3. How to maintain?



After installed. Wait 12 hours before wiping the protected panel.



Simply use water & microfiber to wipe panels.



Avoid using harsh chemicals may damage film layers.



No high-pressure rubbing may lift up film edges.



Clean stubborn stain with alcohol.

4. How to apply installation:

Clean & wipe the designated panel.



Mist the slip solution on the panel.

Peel the film off and spray slip solution on the film's adhesive side.




Lay the film on the panel.

Align the film with more slip solution.



Wet the surface of the film with slip solution.

Squeeze out water and air bubbles.



Tool Required: Microfiber Towel | Squeegee | Slip Solution | Tack Solution | Head lamp & Heat Gun (optional)

Allow the film to cure for 3 hours and inspect edges.

For better adhesion, go over edges with a hair dryer.





filtered water.

8 Water

Slip Solution: add 1-2 drops of baby Shampoo per 8oz spray bottle of distilled or



8 Wate 2 Isopropyl Alcohol

Tack Solution: add 9 parts of distilled water to 1 part of 70% or 90% isopropyl alcohol. For more aggressive adhesion, add 8 parts of distilled water to 2 parts of alcohol.

(Optional)

